


REMACHE TUBULAR FLOR - ALUMINIO / ACERO

ALUMINUM / STEEL PEEL DOMED HEAD BLIND RIVET
 RIVET TUBULAIRE ECLATE EN ALUMINIUM / ACIER
 SCHÄLEN GEWÖLBTKOPF-BLINDNIETE AUS ALUMINIUM / STAHL



CAJA / BOX / BOÎTE		ALUMINIO / ALUMINIUM		ACERO / STEEL	
CÓDIGO	MEDIDA	RANGO AGARRE			
Code / Code	Measure / Mesure	Grip range / Gamme de prise			
	ØxL	G			
	m.m.	m.m.			
RESAF4010	4,0x10	2,5-5,0		500	10.000
RESAF4012	4,0x12	4,5-7,0		500	10.000
RESAF4014	4,0x14	6,5-8,0		500	10.000
RESAF4016	4,0x16	7,5-10,0		500	10.000
RESAF4018	4,0x18	9,5-12,0		500	10.000
RESAF4020	4,0x20	11,5-14,0		500	5.000
RESAF4025	4,0x25	13,5-19,0		250	5.000
RESAF4810	4,8x10	2,0-4,0		500	5.000
RESAF4812	4,8x12	3,5-6,0		500	5.000
RESAF4814	4,8x14	5,5-8,0		500	5.000

CAJA / BOX / BOÎTE		ALUMINIO / ALUMINIUM		ACERO / STEEL	
CÓDIGO	MEDIDA	RANGO AGARRE			
Code / Code	Measure / Mesure	Grip range / Gamme de prise			
	ØxL	G			
	m.m.	m.m.			
RESAF4816	4,8x16	7,5-10,0		500	5.000
RESAF4818	4,8x18	9,5-12,0		500	5.000
RESAF4821	4,8x21	12,5-15,0		250	5.000
RESAF4824	4,8x24	14,5-18,0		250	5.000
RESAF4830	4,8x30	20,5-24,0		250	2.500
RESAF4835	4,8x35	-		200	2.000
RESAF4840	4,8x40	28,5-34,0		150	1.500
RESAF4845	4,8x45	-		100	1.200
RESAF4850	4,8x50	-		100	1.200

AUTOSERVICIO		ALUMINIO / ALUMINIUM		ACERO / STEEL	
CÓDIGO	MEDIDA				
Code / Code	Measure / Mesure				
	ØxL				
	m.m.				
BFRESAF4816	4,8x16	100	12		
BFRESAF4821	4,8x21	75	12		
BFRESAF4824	4,8x24	75	12		
BFRESAF4830	4,8x30	50	12		
BFRESAF4835	4,8x35	50	12		

BLISTER / BLISTER / BLISTER		ALUMINIO / ALUMINIUM		ACERO / STEEL	
CÓDIGO	MEDIDA				
Code / Code	Measure / Mesure				
	ØxL				
	m.m.				
BRESAF4816	4,8x16	10	20		
BRESAF4821	4,8x21	10	20		
BRESAF4824	4,8x24	10	20		
BRESAF4830	4,8x30	8	20		
BRESAF4835	4,8x35	5	20		

PEDIDO MÍNIMO 1 EMBALAJE / MINIMUM ORDER 1 PACKAGING / COMMANDE MINIMALE 1 EMBALLAGE / MINDESTBESTELLMENGE 1 VERPACKUNG

INFORMACIÓN TÉCNICA / TECHNICAL INFORMATION

Ø	D	H	T	P min.	W nom.	CIZALLA TÍPICA	TRACCIÓN TÍPICA	Ø AGUJERO
						Typical shear	Typical tensile	Hole Ø
						Cisaillement typique	Traction typique	Ø Foret
m.m.	m.m.	m.m.	m.m.	m.m.	m.m.	N min.	N min.	m.m.
4,0	3,85-4,15	7,0-8,0	1,5	27	2,22	1.160	1.560	4,3-4,4
4,8	4,65-4,95	8,5-9,5	1,6	27	2,72	1.690	2.230	5,1-5,2

