







## TORNILLO DIRECTO HORMIGÓN

 DIRECT FIXING SCREW FOR CONCRETE WITH HEXAGONAL HEAD  
 VIS DE FIXATION DIRECTE POUR LE BÉTON AVEC TÊTE HEXAGONALE  
 GERADE-SECHSKANTBETONSCHRAUBE





CAJA / BOX / BOÎTE 

CINCADO / ZINC PLATED

CÓDIGO Code / Code	MEDIDA Measure / Mesure ØxL m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	GROSOR A FIJAR Thickness to fix / Épaisseur tfix m.m.	LLAVE Wrench / Clé SW	*CC.		PROF. TALADRO Hole depth / Prof. trou h1 m.m.		
					Extracción tension load / extraction kN	Cizallado shear load / cisaillement kN			
THE078060	8x60	6	10	10	7,60	8,5	65	100	1.000
THE078080	8x80	6	20	10	11,2	8,5	75	50	500
THE100060	10x60	8	10	13	9,2	10,5	70	50	500
THE100080	10x80	8	10	13	15,6	18,1	90	50	500
THE100100	10x100	8	30	13	15,6	18,1	90	25	250
THE100140	10x140	8	70	13	15,6	18,1	90	25	250
THE120090	12x90	10	10	15	22,5	29,2	100	25	250
THE120110	12x110	10	30	15	22,5	29,2	100	25	250
THE120130	12x130	10	50	15	22,5	29,2	100	25	250




AUTOSERVICIO / SELF-SERVICE / AUTO-SERVICE 

CINCADO / ZINC PLATED


CÓDIGO Code / Code	MEDIDA Measure / Mesure ØxL m.m.		
BFTHE080060	8x60	10	12
BFTHE080080	8x80	8	12
BFTHE100060	10x60	8	12
BFTHE100080	10x80	6	12
BFTHE100100	10x100	4	12

PEDIDO MÍNIMO 1 EMBALAJE / MINIMUM ORDER 1 PACKAGING  
COMMANDE MINIMALE 1 EMBALLAGE / MINDESTBESTELLMENGE 1 VERPACKUNG



## TORNILLO DIRECTO HORMIGÓN HEXAGONAL INOXIDABLE A-4

 SS. AISI 316 DIRECT FIXING SCREW FOR CONCRETE WITH HEX. HEAD  
 FIXATION DIRECTE POUR LE BÉTON AVEC TÊTE HEXAGONALE INOX. A-4  
 GERADE-SECHSKANTBETONSCHRAUBE AUS EDELSTAHL A-4



CAJA / BOX / BOÎTE 

INOX. A-4 / S.S. AISI 316

CÓDIGO Code / Code	MEDIDA Measure / Mesure ØxL m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	GROSOR A FIJAR Thickness to fix / Épaisseur tfix m.m.	LLAVE Wrench / Clé SW	*CC.		PROF. TALADRO Hole depth / Prof. trou h1 m.m.		
					Extracción tension load / extraction kN	Cizallado shear load / cisaillement kN			
THE408065	8x65	6	5	10	12,50	9,75	70	100	1.000
THE408080	8x80	6	20	10	12,50	9,75	70	50	500
THE408100	8x100	6	40	10	12,50	9,75	70	50	500
THE408140	8x140	6	80	10	12,50	9,75	70	50	500
THE410080	10x80	8	10	13	23,00	17,50	90	50	500
THE410100	10x100	8	30	13	23,00	17,50	90	25	250
THE410140	10x140	8	70	13	23,00	17,50	90	25	250

## INFORMACIÓN TÉCNICA / TECHNICAL INFORMATION

