


## ZAMAK TORNILLO CABEZA HEXAGONAL

SLEEVE ANCHOR ZAMAK WITH FIXED CONE AND HEXAGONAL HEAD SCREW  
 CHEVILLE À DOUILLE ZAMAK AVEC CÔNE FIXE ET VIS TÊTE HEXAGONAL  
 HÜLSENANKER MIT FESTEM KONUS UND SECHSKANTSCHRAUBE



CAJA / BOX / BOÎTE

CINCADO / ZINC PLATED

CÓDIGO Code / Code	MEDIDA Measure / Mesure MxL/Ø m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	LLAVE Wrench / Clé SW	*CR.			
				Extracción	Cizallado		
				tension load / extraction daN	shear load / cisaillement daN		
ZT06	<b>M6x45/Ø12</b>	12	10	300	400	100	1.200
ZT08	<b>M8x60/Ø14</b>	14	13	400	500	50	300
ZT10	<b>M10x70/Ø16</b>	16	17	500	700	50	300
ZT12	<b>M12x80/Ø20</b>	20	19	600	800	25	150

## ZAMAK ARO

SLEEVE ANCHOR ZAMAK WITH FIXED CONE AND EYE  
 CHEVILLE À DOUILLE ZAMAK AVEC CÔNE FIXE ET PITON  
 HÜLSENANKER MIT FESTEM KONUS UND AUGENSCHRAUBE



CAJA / BOX / BOÎTE

CINCADO / ZINC PLATED

CÓDIGO Code / Code	MEDIDA Measure / Mesure MxL/Ø m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	LLAVE Wrench / Clé SW	*CR.			
				Extracción	Cizallado		
				tension load / extraction daN	shear load / cisaillement daN		
ZA06	<b>M6x45/Ø12</b>	12	10	300	400	100	600
ZA08	<b>M8x60/Ø14</b>	14	13	400	500	50	300
ZA10	<b>M10x70/Ø16</b>	16	17	500	700	25	150
ZA12	<b>M12x80/Ø20</b>	20	19	600	800	20	120

## ZAMAK GANCHO

SLEEVE ANCHOR ZAMAK WITH FIXED CONE AND HOOK  
 CHEVILLE À DOUILLE ZAMAK AVEC CÔNE FIXE ET CROCHET  
 HÜLSENANKER MIT FESTEM KONUS UND RUNDHAKEN



CAJA / BOX / BOÎTE

CINCADO / ZINC PLATED

CÓDIGO Code / Code	MEDIDA Measure / Mesure MxL/Ø m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	LLAVE Wrench / Clé SW	*CR.			
				Extracción	Cizallado		
				tension load / extraction daN	shear load / cisaillement daN		
ZG06	<b>M6x45/Ø12</b>	12	10	110	400	100	600
ZG08	<b>M8x60/Ø14</b>	14	13	150	500	50	300
ZG10	<b>M10x70/Ø16</b>	16	17	230	700	25	150
ZG12	<b>M12x80/Ø20</b>	20	19	330	800	20	120

## ZAMAK CÁPSULA

SLEEVE ANCHOR ZAMAK WITH FIXED CONE  
 CHEVILLE À DOUILLE ZAMAK AVEC CÔNE FIXE  
 HÜLSENANKER MIT FESTEM KONUS



CAJA / BOX / BOÎTE

CINCADO / ZINC PLATED

CÓDIGO Code / Code	MEDIDA Measure / Mesure MxL/Ø m.m.	Ø BROCA Drill Ø / Ø Foret D m.m.	*CR.			
			Extracción	Cizallado		
			tension load / extraction daN	shear load / cisaillement daN		
ZC06	<b>M6x45/Ø12</b>	12	300	400	100	1.200
ZC08	<b>M8x60/Ø14</b>	14	400	500	50	300
ZC10	<b>M10x70/Ø16</b>	16	500	700	50	300
ZC12	<b>M12x80/Ø20</b>	20	600	800	25	150

\* Recomendamos aplicar un coeficiente de seguridad "4" / We recommend applying a safety factor of "4"

/ Nous recommandons d'appliquer un facteur de de sécurité "4" / Wir empfehlen die Anwendung eines Sicherheitsfaktors von "4"

CR.: Carga recomendada, PA.: Par de apriete. / CR.: Recommended loads, PA.: Torque / CR.: Charges recommandées, PA.: Couple de serrage / CR.: Empfohlene Lasten, PA.: Anzugsrehmoment.